



# MATERIAL SAFETY DATA SHEET

## SECTION 1 : IDENTIFICATION

**PRODUCT :** Particleboard (Phenol-Formaldehyde Bonded)  
Raw and Laminated

**PRODUCT NAME :** All particleboard products

**MANUFACTURIER :** Uniboard™

**ADRESSE :** 2540, boulevard Daniel Johnson, bureau 500  
Laval Québec – H7T 2S3

**TELEPHONE :** (514) 682-5240

**FAX :** (514) 682-0550

**DATE PREPARED/REVISED :** Mai 20, 2008

## SECTION 2 : HAZARDOUS INGREDIENTS<sup>1</sup>

Under some conditions, the following hazardous chemicals or components may be released from particleboard and/or products manufactured from same. Wood dust may also be developed from machining form various wood products.

<b>Chemical Component</b>	<b>(CAS 1)</b>	<b>ACGIH TLV</b>	<b>OSHA PEL</b>
Formaldehyde	50-00-0	Ceiling 0.3 ppm	TWA 0.75 ppm STEL 2.0 ppm
Wood dust	N/A	TWA 5 mg/m <sup>3</sup> (softwood) STEL 10 mg/m <sup>3</sup> (softwood) STEL 1 mg/m <sup>3</sup> (beach and oak)	TWA 5 mg/m <sup>3</sup> (all except Red Cedar) STEL 10 mg/m <sup>3</sup> (all except Red Cedar) STEL 2.5 mg/m <sup>3</sup> (Western Red Cedar)

<sup>1</sup> OSHA = Occupational Safety & Health Administration  
ACGIH = American Conference of Governmental Industrial Hygienists  
PEL = Permissible Exposure Limit  
TWA = Time Weighted Average  
TLV = Threshold Limit Value – recommended level  
STEL = Short Term Exposure Limit (15-minutes)  
Ceiling Limit in the work environnement- never to be exceeded

