

MATERIAL SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION

PRODUCT : Particleboard (Urea-Formaldehyde Bonded)
Raw and Laminated

PRODUCT NAME : All particleboard products

MANUFACTURIER : Uniboard™

ADRESSE : 2540, boulevard Daniel Johnson, bureau 500
Laval Québec – H7T 2S3

TELEPHONE : (514) 682-5240

FAX : (514) 682-0550

DATE PREPARED/REVISED : Mai 20, 2008

SECTION 2 : HAZARDOUS INGREDIENTS¹

Under some conditions, the following hazardous chemicals or components may be released from particleboard and/or products manufactured from same. Wood dust may also be developed from machining form various wood products.

Chemical Component	(CAS 1)	ACGIH TLV	OSHA PEL
Formaldehyde	50-00-0	Ceiling 0.30 ppm	TWA 0.75 ppm STEL 2.0 ppm
Wood dust	N/A	TWA 5 mg/m ³ (softwood) STEL 10 mg/m ³ (softwood) STEL 1 mg/m ³ (beach and oak)	TWA 5 mg/m ³ (all except Red Cedar) STEL 10 mg/m ³ (all except Red Cedar) STEL 2.5 mg/m ³ (Western Red Cedar)

¹Notes:

- OSHA = Occupational Safety & Health Administration
- ACGIH = American Conference of Governmental Industrial Hygienists
- PEL = Permissible Exposure Limit
- TWA = Time Weighted Average
- TLV = Threshold Limit Value – recommended level
- STEL = Short Term Exposure Limit (15-minutes)
- Ceiling Limit in the work environnement- never to be exceeded

